








AC SERVO MOTORS



TECO Electric & Machinery Co., Ltd

10F No. 3-1, Yuan Cyu St. Nan-Kang Taipei 115 Taiwan ROC

Tel : +886 2 6615 9111

Web : [http:// www.tecomotor.com.tw](http://www.tecomotor.com.tw)

Performance Data

Model		Unit	TSB18302H3	TSB18552H3	TSB18752H3	TSB22113H3(A)	TSB22113H3(B)	TSB22153H3
Rated Output		kW	3	5.5	7.5	11	11	15
Voltage		V	220	220	220	220	220	220
Rated Torque		N.m	19.1	35.1	47.8	88.0	70.1	95.5
Rated Current		A(rms)	23.0	42.1	58.0	54.0	58.0	78.0
Rated Speed		rpm	1500			1200	1500	
Max. Speed		rpm	3000			1500	2000	
Instantaneous Max. Torque		N.m	49.5	89.6	122.6	222.0	179.0	243.0
Instantaneous Max. Current		A(rms)	59.8	109.5	151.0	142.0	152.0	204.0
Torque Constant		N-m/Arms	0.83	0.83	0.82	1.63	1.21	1.22
Back EMF Constant		Vrms/krpm	54.21	53.27	53.748	115.98	86.98	86.98
Rotor Moment of Inertia		$\times 10^{-4}$ (Kg. m ²)	39.99	63.52	93.94	237.93	199.75	237.93
Resistance		Ω	0.092	0.038	0.027	0.032	0.033	0.018
Inductance		mH	1.507	0.764	0.490	1.189	0.816	0.679
Machanical Time Constant		ms	0.809	0.543	0.569	0.403	0.619	0.394
Electrical Time Constant		ms	16.38	20.11	18.13	37.15	24.72	37.70
Insulation Grade			F					
Weight		kgf	19.5	28.5	42	58	46	58
Installation Dimension	LA	mm	200	200	200	235	235	235
	LB	mm	114.3	114.3	114.3	200	200	200
	LC□	mm	180	180	180	220	220	220
	LZ	mm	13.5	13.5	13.5	13.5	13.5	13.5
Length	L	mm	322	393	484	542	502	542
	LL	mm	243	280	371	426	386	426
	Q	mm	79	113	113	116	116	116
	LE	mm	3.2	3.2	3.2	4	4	4
Shaft	S	mm	35	42	42	42	42	42
	W	mm	10	12	12	12	12	12
	T	mm	8	8	8	8	8	8
	U	mm	5	5	5	5	5	5
	DH	mm	M12 x 24	M16 x 32	M16 x 32	M16 x 32	M16 x 32	TBD

Dimensions in mm

